

Race invitation to:

NEZ and WC Warm-Up 7.-10.6.2018

Address: Kuninkaantie 1, 65300 VAASA

Classes: F1-32, ES-32, PR-24 (=individual) and ES-24

Rules

- All classes according to ISRA rules
- PR24 technical exceptions end of this document

Race format for all classes:

- qualification, direct finals 8*5min
- prizes for Top8, TQ and Councourse!

Entry fee: 10€/ class, payment in cash! + 22€ from PR-24 handout tires.

- Suomalaisille kilpailijoille maksut Autorataharrastajat ry tilille FI47 5028 0920 0212 81
 - o Viestikenttään : KITIn viitenumero –niillä ketkä ilmoittautuu KITIn kautta.

Preliminary time schedule:

Wed 6.6. 9:00 – 20:00 Free practice

Thu 7.6. 8:00-

- Formula 1-32
 - o 3? hours ticket practice, qualification, 8*5min finals
- EuroSport-32
 - o 1,5? hours ticket practice

Fri 8.6. 8:00-

- EuroSport-32
 - o 1,5? hours ticket practice, qualification, 8*5min finals
- Production-24
 - o 1,5? hours ticket practice

Sat 9.6. 8:00-

- Production-24
 - o 1,5? hours ticket practice, qualification, 8*5min finals

Sun 10.6. 8:00-

- EuroSport-24
 - o 3? hours ticket practice, qualification, 8*5min finals

Registration for Finnish drivers will be to AKK- KITI.

- From overseas via email - tuomo_iso-aho@hotmail.com

latest registered date is Wednesday 30.5.2018 22:00!

Race organizer: Tuomo "Tumppi" Iso-Aho, tuomo_iso-aho@hotmail.com, +358400936704

Welcome to the Vaasa !

PR24 race exceptions:

- **Tires:** Handout. Same tires as in the World Championship. 2 pairs per racer.
- **Bodyshell:** No Handout. Lada Vesta WTCC 2017 by Redfox. Thick or thin versions (0.007", 0.005") are legal. Driver not required.
- **Motor:** No Handout.

* **Cans, magnets and endbells** from the following manufacturers allowed:
CHAMPION X12, PROSLOT X12, KOFORD X12, RED FOX

- Motor parts can be freely mixed with each other.
- C-can with minimum inside dimensions: height 14.2 mm, diameter 21.2 mm, length 23.5 mm.
- You can only grind notch at the point of contact with rear axle.
- Only plastic endbells from manufacturers list above allowed. No other modifications allowed than the endbell bottom to allow proper mounting to the chassis.
- Brushes may be shunted.
- It is allowed to replace Oilite Bushings with Ball Bearings.

* **Magnets:** Single ceramic magnets from manufacturers mentioned above. Minimum dimensions: height 14 mm, length 11.5 mm. You can only grind notch at the point of contact with rear axle, regrind inner side of magnet and roughen surface for gluing.

* **Armature:** Mass-produced, labeled X12, ISRA 12, UA 12 or similar from Proslot, Koford and Valiko, wire diameter 0.285 mm (AWG 29). Minimum lamination diameter 13.03 mm, maximum 13.16 mm. Motor shaft diameter 2 mm.